

We develop **Systems** to meet
your needs



Thrombotimer

Our specialists for blood plasma

- Can be used with all reagents
- Automatic start upon dispensing reagent
- Employs an opto-mechanical measuring system
- Maintenance-free

The principle is simple

Starting

When switched on, the Thrombotimer automatically checks all important functions.

Incubating

Inserting a cuvette with a sample into the incubation position will automatically start the timed incubation process.

Measuring

Upon completion of incubation, the cuvette is placed in the measuring channel. The reagent is then added with any commercial pipette. The system starts upon reagent addition and stops with the coagulation of the sample. All results are automatically calculated and then displayed.

Every detail is innovative

The opto-mechanical measuring system

A circulating magnet underneath the cuvette causes a steel ball to rotate. This ball optimises the gentle mixing of the sample which results in uniform coagulation. The light source is adjusted according to the sample's turbidity making it possible to measure even difficult samples reliably. All sensors in the measuring system are protected from becoming soiled.

The incubation

A timer determines the period of incubation. Shortly before the completion of incubation, a red LED flashes. When incubation is complete, the Thrombotimer emits an acoustic signal. The timer can be programmed as needed for each test.



The evaluation

The measuring results are displayed %, INR, Ratio, mg/dl, g/l or seconds. A PC or printer may also be connected to the Thrombotimer.

The service

Since its introduction, the Thrombotimer has proved to be a maintenance-free instrument. Transmission of measuring data to an external system is made possible with the integrated interface.

The Thrombotimer at a glance

	Thrombotimer 1	Thrombotimer 2	Thrombotimer 4
Measuring channels	1	2	4
Incubation positions	2	4	8
Reagent positions	2	2	4
Double determination	–	✓	✓
All standard reagents	✓	✓	✓
Processes calibration curves	✓	✓	✓
Test-specific incubation times	✓	✓	✓
RS232 interface (PC/Printer)	✓	✓	✓
Operating voltage	115/230 V, 50–60 HZ	115/230 V, 50–60 HZ	115/230 V, 50–60 HZ
Power consumption	20 VA	20 VA	30 VA
Dimensions (W x H x L)	125 x 105 x 305 mm	125 x 105 x 305 mm	250 x 125 x 325 mm
Weight	2.2 kg	2.2 kg	5 kg
Shipment includes	Mains cable, ball dispenser, dust cover, consumables for the first tests		
Optional	Thermoprinter		

Behnk Elektronik

Behnk Elektronik GmbH & Co. KG

Hans-Böckler-Ring 27

22851 Norderstedt

Germany

Telephone +49 (0) 40 - 529 86 10

Telefax +49 (0) 40 - 524 10 94

Web www.behnk.de

E-mail info@behnk.de

Thrombotimer

Innovative.

Reliable.

Maintenance-free.